

CANNON



Dimensions	: 604 x 261 x 481 mm (DWH)
Form Factor	: Full Tower
Materials	: Aluminum + Plastic + Steel
Mainboard Support	: E-ATX, ATX, Micro-ATX, Mini-ITX
I/O Ports	: Power, USB 3.0 x 2, USB 3.1 Type-C x 1, Headphone/Mic Combo Jack
Side Panel	: 4mm Tempered glass
Expansion & Drive Bays	: 3.5" x 1; 2.5" x 2
Cooling Support	: Front: 3 x 120mm; Side: 6 x 120mm; Rear: 3 x 120mm / 3 x 140mm
Radiator Support	: Front: 120 / 240 / 360mm; Side: 120 / 240 / 360mm (Support up to 2 x 360mm Radiators at the same time); Rear: 120 / 140 / 240 / 280 / 360 / 420mm
Max GPU Length	: ≤ 385mm
Max CPU Cooler Height	: ≤ 85mm
Max PSU Length	: ≤ 270mm
Gross Weight	: 13.3kgs



CASING DESIGN



A New Angle of Innovation

TORQUE

BLACK/WHITE



Dimensions	: 621 x 285 x 644 mm (DWH)
Form Factor	: Mid Tower
Materials	: Aluminum
Mainboard Support	: E-ATX, ATX, Micro-ATX, ITX
Front Access & Controls	: USB3.0 x 2, MIC/AUDIO (HD), Power, Type-C USB3.1
Side Panel	: 4mm Tempered glass (Both sides)
Expansion Slots	: 7; Drive bays: 3.5" x 1; 2.5" x 1
Cooling Support	: Front: 3 x 120mm; Top: 3 x 120mm; Rear: ≤ 360mm; Top: ≤ 360mm
Radiator Support	: Front: ≤ 360mm; Top: ≤ 360mm
MB Tray Clearance	: ≤ 37mm;
Max GPU Length	: ≤ 450mm
Max CPU Cooler Height	: ≤ 215mm
PSU Support	: ATX
Gross Weight	: 14.25kgs



CASING DESIGN



P120 CRYSTAL WHITE



Dimensions	: 476 x 234 x 485mm (DWH)
Form Factor	: Mid Tower
Materials	: Steel
Mainboard Support	: E-ATX, ATX, M-ATX, ITX
Front Access & Controls	: Power, Reset, White LED USB3.0 x 2, HD-AUDIO
Side Panel	: Tempered Glass
Expansion Slots	: 7 (Horizontal) + 3 (Vertical); Drive bays: 3.5" / 2.5" x 2 / 1; 2.5" x 3
Cooling Support	: Bottom: 3 x 120mm / 3 x 140mm; Rear: 1 x 120mm or 1 x 140mm; M/B Side: Up to 3 x 120mm or 2 x 140mm (1 x HDD bracket needs to be removed when installing 3 x 120mm)
Radiator Support	: Bottom: Up to 360mm (≤ 28mm Thickness); Rear: Up to 120 mm (Limited Radiator Length ≤ 160mm); M/B Side: Up to 360mm (Radiator length < 400mm, remove one bracket Radiator Length ≥ 400mm, remove both brackets)
Max GPU Length	: ≤ 450mm
Max CPU Height	: ≤ 185mm
Max PSU Support	: ≤ 294mm
Dust Filter	: Bottom/Right Side Panel
Gross Weight	: 12.4kgs

NX700



Dimensions	: 440 X 220 x 492mm(DWH)
Form Factor	: Mid Tower
Materials	: SPCC + Plastic
Mainboard Support	: ATX, Micro-ATX, ITX
Front Access & Controls	: Power, LED control button, USB 3.0 x 2, MIC / HD-AUDIO
Side Panel	: 4mm Tempered Glass
Expansion Slots	: 7; Drive bays: 3.5" / 2.5" (Convertible) x 2/2 2.5" x 4
Cooling Support	: Front: 3 x 120mm / 3 x 140mm / 2 x 185 mm; Top: 2 x 120mm / 2 x 140 mm; Power Supply Shroud: 2 x 120mm; Rear: 1 x 120mm
Radiator Support	: Front: 120 / 140 / 240 / 280 / 360 mm; Top: 120 / 140 / 240 / 280 mm; Rear: 120 mm
Max GPU Length	: ≤ 340mm
Max CPU Cooler Height	: ≤ 170mm
PSU Length	: ≤ 200mm (with HDD) ≤ 365mm (without HDD)
Dust Filter	: Top/Bottom
Gross Weight	: 7.9kgs

Includes:
2 x 185mm ARGB fans in front
1 x 120mm ARGB fan in rear

DF800 Flux



Dimensions	: 479 x 220 x 488 mm (DWH)
Form Factor	: Mid Tower
Materials	: Steel + Plastic
Mainboard Support	: ATX, Micro-ATX, Mini-ITX
Front Access & Controls	: Power, LED Control Button, 2 x USB3.0, MIC/HD-AUDIO
Side Panel	: 4mm Tempered Glass Side Panel
Expansion Slots	: 7; Drive bays: 3.5" x 3; 2.5" x 3
Cooling Support	: Front: 3 x 120mm / 3 x 140mm; Top: 3 x 120mm / 2 x 140mm; Rear: 1 x 120mm; PSU Shroud: 2 x 120mm
Radiator Support	: Front: 120 / 240 / 280 / 360mm; ≤ 55mm thickness (fans installed outside of the front panel) ≤ 30mm thickness (fans installed inside of the front panel) Top: 120 / 240 / 280 / 360mm; Rear: 120mm
Max GPU Length	: ≤ 405mm
Max CPU Cooler Height	: ≤ 175mm
PSU Support	: ≤ 205mm
Dust Filter	: Top / Bottom / Right Hand Side
Gross Weight	: 8.70 kg

DF600 Flux



Dimensions	: 467 x 220 x 486 mm (DxWxH)
Form Factor	: Mid Tower
Materials	: Steel + Plastic
Mainboard Support	: ATX, Micro-ATX, Mini-ITX
Front Access & Controls	: Power, LED Control Button, 2 x USB3.0, HD-AUDIO
Side Panel	: 4mm Tempered Glass Side Panel
Expansion Slots	: 7; Drive bays: 3.5" / 2.5" (Convertible) x 3 / 2; 2.5" x 3
Cooling Support	: Front: 3 x 120 / 140mm; Top: 3 x 120 / 2 x 140mm; Rear: 1 x 120; PSU Shroud: 2 x 120mm
Radiator Support	: Front: 120 / 240 / 280 / 360mm; ≤ 55mm thickness (fans installed outside of the front panel) ≤ 30mm thickness (fans installed inside of the front panel) Top: 120 / 240 / 280 / 360mm; Rear: 120mm
Max GPU Length	: ≤ 405mm
Max CPU Cooler Height	: ≤ 175mm
PSU Support	: ≤ 205mm
Dust Filter	: Front / Top / Bottom / Right hand side
Gross Weight	: 8.51 Kgs

Includes:
3 x 120 mm ARGB fans in front
1 x 120 mm fan (Reverse Fan) on PSU shroud
& 1 x 120 mm fan in rear

Note: ARGB & PWM Fan Controller

Includes:
3 x 120mm ARGB fans in front
1 x 120mm fan (Reverse Fan) on PSU shroud
& 1 x 120mm fan in rear

Note: ARGB & PWM Fan Controller

AX90

NEW



Dimensions	: 473 x 210 x 486 mm (DxWxH)
Form Factor	: Mid Tower
Materials	: Steel + Plastic
Mainboard Support	: ATX, Micro-ATX, ITX
Front Access & Controls	: Power, Reset, LED Control Button, 1 x USB3.0, 2 x USB2.0, MIC/HD-AUDIO
Side Panel	: 4mm Tempered Glass
Expansion Slots	: 7; Drive bays: 3.5"/2.5" x 2 / 1; 2.5" x 2
Cooling Support	: Front: 3 x 120 / 3 x 140mm; Top: 3 x 120 / 2 x 140mm; PSU Shroud: 2 x 120; Side: 2 x 120mm; Rear: 1x120
Radiator Support	: Front: 120/140/240/280/360mm; Top: 120/140/240/280/360mm; Side: 120 / 240mm; Rear: 120mm
Max GPU Length	: ≤ 385mm
Max CPU Cooler Height	: ≤ 160mm
PSU Support	: ≤ 220mm (with HDD) ≤ 410mm (without HDD)
Dust Filter	: Front / Top / Bottom / Right Hand Side
Gross Weight	: 7.93 Kgs

Includes:
3 x 120 mm ARGB fixed fans in the front + 1 x 120mm ARGB fan in rear

NX410 White



Dimensions	: 390 x 210 x 485 mm
Form Factor	: Mid Tower
Materials	: SPCC + ABS
Mainboard Support	: ATX, micro-ATX, ITX
Front Access & Controls	: Power, LED Control Button, USB2.0 x2, USB3.0 x 1, HD-Audio
Side Panel	: Tempered Glass Side Panel
Expansion Slots	: 7; Drive bays: 3.5" / 2.5" (Convertible) x 2 / 1; 2.5" x 3
Cooling Support	: Front: 3 x 120mm / 3x140mm; Top: 2 x 120mm / 2 x140mm; Rear: 1 x 120mm
Radiator Support	: Front: ≤ 120 mm / 240 mm / 280 mm / 360 mm; Top: ≤ 120mm / 240 m / 280mm; Rear: 120mm
Max GPU Length	: ≤ 335mm
Max CPU Cooler Height	: ≤ 168mm
PSU Support	: ≤ 165mm
Dust Filter	: Top / Bottom
Gross Weight	: 6.3kgs

Includes:
2 x 140 mm ARGB fan in front
1 x 120 mm ARGB fan in rear

NX410 Black



Dimensions	: 390 x 210 x 485 mm
Form Factor	: Mid Tower
Materials	: SPCC + ABS
Mainboard Support	: ATX, micro-ATX, ITX
Front Access & Controls	: Power, LED Control Button, USB2.0 x2, USB3.0 x 1, HD-Audio
Side Panel	: Tempered Glass Side Panel
Expansion Slots	: 7; Drive bays: 3.5" / 2.5" (Convertible) x 2 / 1; 2.5" x 3
Cooling Support	: Front: 3 x 120mm / 3x140mm; Top: 2 x 120mm / 2 x140mm; Rear: 1 x 120mm
Radiator Support	: Front: ≤ 120 mm / 240 mm / 280 mm / 360 mm; Top: ≤ 120mm / 240m / 280mm; Rear: 120mm
Max GPU Length	: ≤ 335mm
Max CPU Cooler Height	: ≤ 168mm
PSU Support	: ≤ 165mm
Dust Filter	: Top / Bottom
Gross Weight	: 6.3kgs

Includes:
2 x 140 mm ARGB fan in front
1 x 120 mm ARGB fan in rear

NX292 White



Dimensions	: 406x 206 x 450mm (DWH)
Form Factor	: Mid Tower
Materials	: Steel + Plastic
Mainboard Support	: E-ATX, ATX, Micro-ATX, ITX
Front Access & Controls	: Power, Reset, USB2.0 x 2, USB3.0 x1, Headphone/Mic combo jack
Side Panel	: Tempered Glass
Expansion Slots	: 7; Drive bays: 3.5"/2.5" x 2 / 1; 2.5" x 2
Cooling Support	: Front: 3 x 120mm / 2 x 140mm; Top: 2 x 120mm / 2 x140mm; Rear: 1 x 120mm; PSU Shroud: 2 x 120mm
Radiator Support	: Front: 120 / 140 / 240 / 280 / 360 mm; Rear: ≤ 120 mm (Length ≤ 156mm)
Max GPU Length	: ≤ 320mm
Max CPU Cooler Height	: ≤ 155mm
PSU Support	: ≤ 165mm(with HDD) ≤ 300mm(without HDD)
Dust Filter	: Top / Bottom
Gross Weight	: 5.3kgs

Includes:
3 x 120mm Fixed mode RGB Fans in front
1 x 120mm regular fan in rear

NX292 Black



Dimensions	: 406x 206 x 450mm (DWH)
Form Factor	: Mid Tower
Materials	: Steel + Plastic
Mainboard Support	: E-ATX, ATX, Micro-ATX, ITX
Front Access & Controls	: Power, Reset, USB2.0 x 2, USB3.0 x1, Headphone/Mic combo jack
Side Panel	: Tempered Glass
Expansion Slots	: 7; Drive bays: 3.5"/2.5" x 2 / 1; 2.5" x 2
Cooling Support	: Front: 3 x 120mm / 2 x 140mm; Top: 2 x 120mm / 2 x140mm; Rear: 1 x 120mm; PSU Shroud: 2 x 120mm
Radiator Support	: Front: 120 / 140 / 240 / 280 / 360 mm; Rear: ≤ 120 mm (Length ≤ 156mm)
Max GPU Length	: ≤ 320mm
Max CPU Cooler Height	: ≤ 155mm
PSU Support	: ≤ 165mm(with HDD) ≤ 300mm(without HDD)
Dust Filter	: Top / Bottom
Gross Weight	: 5.3kgs

Includes:
3 x 120mm Fixed mode RGB Fans in front
1 x 120mm regular fan in rear

NX291



Dimensions	: 405 x 206 x 450mm (DWH)
Form Factor	: Mid Tower
Materials	: Steel + Plastic
Mainboard Support	: E-ATX, ATX, Micro-ATX, ITX
Front Access & Controls	: Power, Reset, USB 2.0 x 2, USB 3.0 x 1, Headphone / Mic Combo Jack
Side Panel	: Tempered Glass
Expansion Slots	: 7; Drive bays: 3.5"/2.5" x 2 / 1; 2.5" x 2
Cooling Support	: Front: 3 x 120mm / 2 x 140mm; Top: 2 x 120mm / 2 x 140 mm; Rear: 1 x 120mm; PSU: 2 x120mm
Radiator Support	: Front: 120 / 140 / 240 / 280 / 360 mm; Rear: 120mm (Length ≤ 156mm)
Max GPU Length	: ≤ 320mm
Max CPU Cooler Height	: ≤ 155mm
PSU Support	: ≤ 165mm (with HDD) ≤ 300mm (without HDD)
Dust Filter	: Top/Bottom
Gross Weight	: 5.3kgs

Includes:
3 x 120mm Fixed Mode RGB fans in front
1 x 120mm regular fan in rear

NX270 TG



Dimensions	: 362 x 217 x 461mm(DWH)
Form Factor	: Mid Tower
Materials	: Steel + Plastic
Mainboard Support	: ATX, Micro-ATX, ITX
Front Access & Controls	: Power, Reset, LED on/off Button, 1 x USB 2.0, 1 x USB3.0, MIC / HD-AUDIO
Side Panel	: Tempered Glass Side Panel
Expansion Slots	: 7; Drive bays: 3.5"/2.5" x 2 / 1; 2.5" x 1
Cooling Support	: Front: 3 x 120mm / 3 x 140mm; Top: 2 x 120mm; Rear: 1 x 120mm; PSU Shroud: 2 x 120mm
Radiator Support	: Front: 120 / 140 / 240 / 280 mm; Top: 120 / 240mm
Max GPU Length	: ≤ 270mm
Max CPU Cooler Height	: ≤ 160mm
PSU Support	: ≤ 160mm (with HDD) ≤ 295mm (without HDD)
Dust Filter	: Top
Gross Weight	: 5.2kgs

Includes:
2 x 120mm RGB fixed model fans in front

AX20



Dimensions	: 358 x 207 x 451 mm (DxWxH)
Form Factor	: Mid Tower
Materials	: Steel + Plastic
Mainboard Support	: ATX, Micro-ATX, ITX
Front Access & Controls	: Power, Reset, 1 x USB3.0 2 x USB2.0, MIC, HD-AUDIO
Side Panel	: Tempered Glass
Expansion Slots	: 7; Drive bays: 2.5" x 2; 3.5"/2.5" Drive Mounts x 2 / 1
Cooling Support	: Front: 3 x 120/2 x 140mm; Top: 2 x 120; Rear: 1x120; PSU Shroud: 2 x 120mm
Radiator Support	: Front: Up to 280mm; Top: Rear:
Max GPU Length	: ≤ 270mm
Max CPU Cooler Height	: ≤ 155mm
PSU Support	: ≤ 170mm (with HDD) ≤ 295mm (without HDD)
Gross Weight	: 4.71 Kgs

Includes:
3 x 120 mm RGB fixed fans in front

NX200M



Dimensions	: 351 x 200 x 390mm (DWH)
Form Factor	: Micro-ATX Mini Tower
Materials	: Steel + Plastic
Mainboard Support	: M-ATX, ITX
Front Access & Controls	: Power, Reset, 1 x USB3.0, 2 x USB 2.0, MIC / HD-AUDIO
Side Panel	: Tempered Glass Side Panel
Expansion Slots	: 4; Drive bays: 3.5"/2.5" x 2 / 1; 2.5" x 1
Cooling Support	: Front: 2x 120mm / 2 x 140mm; Top: 2 x 120mm; Rear: 1 x 120mm
Radiator Support	: Front: 120 / 140 / 240mm; Rear: 120 mm
Max GPU Length	: ≤ 275mm
Max CPU Height	: ≤ 150mm
PSU Support	: ≤ 150mm
Dust Filter	: Bottom
Gross Weight	: 4.34kgs

Includes:
1 x 120mm fan in rear

SIGNATURE PLATINUM SP1300

Fully Modular Power Supply



Rated Power : 1300W
 Modular : Fully
 Type : ATX
 PFC Type : A-PFC/PFC @Half/Full load
 100V-240V
 Energy Rating: 80 Plus Platinum
 Efficiency : at 20%/50%/100% load AC 115V
 Internal, the power efficiency
 should be at least 90%/92%/89%
 Protection : OCP / OVP / UVP / SCP / OPP / OTP /
 SIP / NLO
 Cooling Fan : 135 x 135 x 25(mm) FDB Silent Fan
 Connector : 1 x MB 24(20 + 4) Pin;
 2 x 8(4 + 4) Pin EPS 12V
 12 x 8(6 + 2) Pin PCI-E;
 14 x SATA; 5 x Molex; 1 x FDD
 Dimension (W x L x H): 150 x 170 x 86mm

SIGNATURE PLATINUM SP1000

Fully Modular Power Supply



Rated Power : 1000W
 Modular : Fully
 Type : ATX
 PFC Type : A-PFC/PFC @Half/Full load 100V-240V
 Energy Rating: 80 Plus Platinum
 Efficiency : at 20%/50%/100% load AC 115V
 Internal, the power efficiency should
 be at least 90%/92%/89%
 Protection : OCP / OVP / UVP / SCP / OPP / OTP /
 SIP / NLO
 Cooling Fan : 135 x 135 x 25(mm) FDB Silent Fan
 Connector : 1 x MB 24(20 + 4) Pin;
 2 x 8(4 + 4) Pin EPS 12V
 8 x 8(6 + 2) Pin PCI-E;
 14 x SATA; 5 x Molex; 1 x FDD
 Dimension (W x L x H): 150 x 170 x 86mm

NE 850GOLD M White

Fully Modular Power Supply



Rated Power : 850W
 Modular : Fully
 Type : ATX 12V 2.4
 PFC Type : A-PFC/100V-240V
 Energy Rating: 80 Plus Gold
 Efficiency : upto 92% Efficiency
 Protection : OCP / OVP / UVP / SCP / OPP / OTP / SIP / NLO
 Cooling Fan : 120mm Silent Fan
 Connector : 1 x MB 24(20+4) Pin;
 2 x 8(4+4) Pin EPS 12V;
 6 x 8(6+2) Pin PCI-E;
 10 x SATA; 5 x Molex;
 1 x FDD
 Dimension (L x W x H): 150 x 140 x 86mm

NE 850GOLD M

Fully Modular Power Supply



Rated Power : 850W
 Modular : Fully
 Type : ATX 12V 2.4
 PFC Type : A-PFC/100V-240V
 Energy Rating: 80 Plus Gold
 Efficiency : upto 92% Efficiency
 Protection : OCP / OVP / UVP / SCP / OPP / OTP / SIP / NLO
 Cooling Fan : 120mm Silent Fan
 Connector : 1 x MB 24(20+4) Pin;
 2 x 8(4+4) Pin EPS 12V
 6 x 8(6+2) Pin PCI-E;
 10 x SATA; 5 x Molex;
 1 x FDD
 Dimension (L x W x H): 150 x 140 x 86mm

NE 750GOLD M

Fully Modular Power Supply



Rated Power : 750W
 Modular : Fully
 Type : ATX 12V 2.4
 PFC Type : A-PFC/100V-240V
 Energy Rating: 80 Plus Gold
 Efficiency : upto 92% Efficiency
 Protection : OCP / OVP / UVP / SCP / OPP / OTP / SIP / NLO
 Cooling Fan : 120mm Silent Fan
 Connector : 1 x MB 24(20+4) Pin;
 2 x 8(4+4) Pin EPS 12V
 4 x 8(6+2) Pin PCI-E;
 8 x SATA; 4 x Molex;
 1 x FDD
 Dimension (L x W x H): 150 x 140 x 86mm

NE 650GOLD M

Fully Modular Power Supply



Rated Power : 650W
 Modular : Fully
 Type : ATX 12V 2.4
 PFC Type : A-PFC/100V-240V
 Energy Rating: 80 Plus Gold
 Efficiency : upto 92% Efficiency
 Protection : OCP / OVP / UVP / SCP / OPP / OTP / SIP / NLO
 Cooling Fan : 120mm Silent Fan
 Connector : 1 x MB 24(20+4) Pin;
 2 x 8(4+4) Pin EPS 12V
 4 x 8(6+2) Pin PCI-E;
 8 x SATA;
 3 x Molex; 1 x FDD
 Dimension (L x W x H): 150 x 140 x 86mm

CSK750H BRONZE

Semi Modular Power Supply



Rated Power : 750W
 Modular : Semi Modular
 Type : ATX 12V 2.31
 PFC Type : A-PFC/100V-240V
 Energy Rating: 80 Plus Bronze
 Efficiency : 88% Efficiency
 Protection : OCP / OVP / UVP / SCP / OPP / NLO / OTP
 Cooling Fan : 120mm Silent Fan
 Connector : 1 x MB 24(20+4) Pin;
 2 x 8(4+4) Pin EPS 12V
 4 x 8(6+2) Pin PCI-E;
 8 x SATA; 3 x Molex;
 Dimension (L x W x H): 150 x 140 x 86mm

ATOM B650 BRONZE

Power Supply



Rated Power : 650W
 Type : ATX 12V 2.31
 PFC Type : A-PFC/200V-240V
 Energy Rating: 80 Plus Bronze
 Protection : OPP/OVP/UVP/SCP
 Connector : 1 x MB 24(20 + 4) Pin;
 1 x 8(4 + 4) Pin EPS 12V
 2 x 8(6 + 2) Pin PCI-E;
 5 x SATA;
 3 x Molex
 Dimension (L x W x H): 150 x 140 x 86mm

SYMPHONY 360 ARGB White CPU LIQUID COOLER

ARGB 3 YEARS WARRANTY

Socket Compatibility
Intel Socket: LGA2066 / 2011 / 1366 / 115X / 1200 / 1700
AMD Socket: FM1 / FM2 / AM4 / AM3 / AM2



FAN	Cooling Type	Water Cooling
	Dimensions	120 x 120 x 25mm
	Type	PWM ARGB LED Fan
	Speed	800-1600rpm±10%
	Airflow	72 CFM Air Pressure : 2.1mm H2o max
RADIATOR	Noise	20-35db (A)
	Lifespan	40k hrs. at 25°C room, ambient 15-65% RH
	Connector	4 pin, ARGB : 3 Pin
	Dimensions	397 x 120 x 27mm
	Material	Aluminum, Polycarbonate
PUMP	Dimensions	66.7 x 67 x 56 mm
	Connector	3 Pin power
	Water Pressure	1.2m
	Flow rate	1.3L/min
	Lifespan	70k hrs. at 25°C room, ambient 15-65% RH
TUBE	Noise	≤ 30dB (A)
	Tube size	8 x 10 x 380 mm

Compatibility: ASUS Aura Sync, MSI Mystic Light Sync, Gigabyte RGB Fusion

SYMPHONY 240 ARGB CPU LIQUID COOLER

ARGB 3 YEARS WARRANTY



FAN	Cooling Type	Water Cooling
	Dimensions	120 x 120 x 25mm
	Type	PWM ARGB LED Fan
	Speed	800-1600rpm±10%
	Airflow	72 CFM Air Pressure : 2.1mm H2o max
RADIATOR	Noise	20-35db (A)
	Lifespan	40k hrs. at 25°C room, ambient 15-65% RH
	Connector	4 pin, ARGB : 3 Pin
	Dimensions	227 x 120 x 27mm
	Material	Aluminum, Polycarbonate
PUMP	Dimensions	66.7 x 67 x 56 mm
	Connector	3 Pin power
	Water Pressure	1.2m
	Flow rate	1.3L/min
	Lifespan	70k hrs. at 25°C room, ambient 15-65% RH
TUBE	Noise	≤ 30dB (A)
	Tube size	8 x 10 x 380 mm

Socket Compatibility
Intel Socket: LGA 1200 / 115X / 1366 / 2011-V3 / 2066
AMD Socket: FM2 / FM1 / AM3+ / AM2+ / AM2 / AM4

Compatibility: ASUS Aura Sync, MSI Mystic Light Sync, Gigabyte RGB Fusion

A400RGB CPU AIR COOLER

3 YEARS WARRANTY



Cooling Type	Air Cooling
Fan Dimensions	125 x 76 x 155 mm (DxWxH)
Type	PWM Silent Fan
Speed	600-1800rpm±10%
Airflow	77 CFM
Noise	20.3-34.5 dBA
Lifespan	50,000 Hours
Connector	4 pin
LED Effect	RGB LED

Socket Compatibility:
Intel: 775/1150/1151/1155/1156/1200/1366/2011/2066
AMD: FM1/FM2/AM3/AM3+/AM2+/AM2/AM4

A40PRO CPU AIR COOLER

3 YEARS WARRANTY



Cooling Type	Air Cooling
Fan Dimensions	92x 92x25 mm (DxWxH)
Type	PWM Silent Fan
Speed	800-2200rpm±10%
Airflow	38 CFM
Noise	16-23 dBA
Lifespan	40,000 Hours
Connector	4 pin
LED Effect	Blue LED

Socket Compatibility:
Intel: 775/1150/1151/1155/1156/1200/1366
AMD: FM1/FM2/FM2+/AM3/AM3+/AM2+/AM2/
APU/A10/A8/A6/A4

A30 OPTIMAL CPU COOLING

3 YEARS WARRANTY



Cooling Type	Air Cooling
Fan Dimensions	92x 92x25 mm (DxWxH)
Type	Silent LED Fan
Speed	1750±10%
Airflow	36 CFM
Noise	20 dBA
Lifespan	50,000 Hours
Connector	3 pin
LED Effect	Blue LED

Socket Compatibility:
Intel: 1150/1151/1155/1200/1155/1156/1700
AMD: FM1/AM3+/AM3+/AM2+/AM2/AM4

PRIZM 120 ARGB 5+C CASE FAN

2 YEARS WARRANTY



5-IN-1 Pack with Fan Controller



Fan Type	PWM Fan
Dimensions (mm)	120*120*25 mm
Bearing Type	Hydraulic
LED Type	Addressable RGB
Fan Speed (RPM)	2000 max.
Airflow (CFM)	45.03 max.
Air Pressure (mmH2O)	2.56 max.
Fan Noise Level (dBA)	32.6 max.
Lifespan	40000 hours
Connector Fan	4 pin ; ARGB: 3 pin
Rated Voltage FAN	DC12V ; LED: DC5V
Operating Voltage FAN	DC6.0-13.8V ; LED: DC4.5-5.3V
Rated Current (A) FAN	0.18A±20% ; LED: 0.80A±20%
Fan Control Box	ARGB port x 5, PWM fan port x 5,SATA, Mode, External LED CTRL,M/B Sync, LED Speed

PRIZM 120 ARGB 3+2+C CASE FAN

2 YEARS WARRANTY



3-IN-1 Pack with Fan Controller & ARGB LED strips



Fan Type	PWM Fan
Dimensions (mm)	120*120*25 mm
Bearing Type	Hydraulic
LED Type	Addressable RGB
Fan Speed (RPM)	2000 max.
Airflow (CFM)	45.03 max.
Air Pressure (mmH2O)	2.56 max.
Fan Noise Level (dBA)	32.6 max.
Lifespan	40000 hours
Connector Fan	4 pin ; ARGB: 3 pin
Rated Voltage FAN	DC12V ; LED: DC5V
Operating Voltage FAN	DC6.0-13.8V ; LED: DC4.5-5.3V
Rated Current (A) FAN	0.18A±20% ; LED: 0.80A±20%
Fan Control Box	ARGB port x 5, PWM fan port x 5,SATA, Mode, External LED CTRL,M/B Sync, LED Speed

PRIZM X 120 ARGB 3+C CASE FAN

2 YEARS WARRANTY



3-IN-1 Pack with Fan Controller



Fan Type	PWM Fan
Dimensions (mm)	120*120*25 mm
Bearing Type	Hydraulic
LED Type	ARGB
Fan Speed (RPM)	500-2000rpm±10%
Airflow (CFM)	0-45.21 CFM
Air Pressure (mmH2O)	0.30-2.56mmH2O
Fan Noise Level (dBA)	20.0-32.6dBA
Lifespan	40000 hours
Connector Fan	4-pin / LED: 3-pin
Rated Voltage FAN	DC12V ; LED: DC5V
Operating Voltage FAN	DC6.0-13.8V ; LED: DC4.5-5.3V
Rated Current (A) FAN	150mA±20% / LED: 900mA(Max)
Fan Control Box	ARGB port x 5, PWM fan port x 5,SATA, Mode, External LED CTRL,M/B Sync, LED Speed

PRIZM 120 ARGB CASE FAN

2 YEARS WARRANTY



Fan Type	PWM Fan
Dimensions (mm)	120*120*25 mm
Bearing Type	Hydraulic
LED Type	Addressable RGB
Fan Speed (RPM)	2000 max.
Airflow (CFM)	45.03 max.
Air Pressure (mmH2O)	2.56 max.
Fan Noise Level (dBA)	32.6 max.
Lifespan	40000 hours
Connector Fan	4 pin ; ARGB: 3 pin
Rated Voltage FAN	DC12V ; LED: DC5V
Operating Voltage FAN	DC6.0-13.8V ; LED: DC4.5-5.3V
Rated Current (A) FAN	0.18A±20% ; LED: 0.80A±20%
Fan Control Box	ARGB port x 5, PWM fan port x 5,SATA, Mode, External LED CTRL,M/B Sync, LED Speed