



Image	Packaging	Model Name	Length	Specifications
CABLE AND EXTENSION				
HDMI CABLE				
		AAIBD	0.5M	Color: Black Connector Type: HDMI A Male Interface Techniques: Gold-plated Transmission Direction: HDMI A Male to HDMI A Male Resolution: 4K@60Hz Conductor: Pure Copper Jacket: PVC Casing: Single-colored Injection Cable OD: 4.7mm
		AAIBF	1M	
		AAIBG	1.5M	
		AAIBH	2M	
		AAIBI	3M	
		AACBF	1M	Color: Black/Blue Connector Type: HDMI A Male Interface Techniques: Gold-plated Transmission Direction: HDMI A Male to HDMI A Male Resolution: 4K@60Hz / 4K@30Hz Conductor: Copper-clad Steel Jacket: PVC Casing: Dual-colored Injection Cable OD: 7.3mm
		AACBG	1.5M	
		AACBH	2M	
		AACBI	3M	
		AACBJ	5M	
		AACBL	10M	
		AACBN	15M	
		ALIBF	1M	Color: Black/Yellow Connector Type: HDMI A Male Interface Techniques: Gold-plated Transmission Direction: HDMI A Male to HDMI A Male Resolution: 4K@60Hz/4K@30Hz Conductor: Copper-clad Steel Jacket: PVC Casing: Dual-colored Injection Cable OD: 7.3mm
		ALIBG	1.5M	
		ALIBH	2M	
		ALIBI	3M	
		ALIBJ	5M	
		ALIBL	10M	
		ALIBN	15M	
		ALGLF	1M	Color: Blue Connector Type: HDMI A Male Interface Techniques: Gold-plated Transmission Direction: HDMI A Male to HDMI A Male Resolution: 8K@60Hz Conductor: Copper-clad steel + Silver ion wire Jacket: PVC & Cotton Braided Casing: Aluminum Alloy Cable OD: 7.3mm
		ALGLH	2M	
		ALGLI	3M	
		ALJBG	1.5M	Color: Black Connector Type: HDMI A Male Interface Techniques: Gold-plated Transmission Direction: HDMI A Male to HDMI A Male Resolution: 4K@60Hz / 4K@30Hz Conductor: Copper-clad Steel Jacket: PVC Casing: Dual-colored Injection Cable OD: 7.3mm
		ALJBH	2M	
		ALJBJ	5M	
		CRBBF	1M	Color: Gray Connector Type: USB-C Male/HDMI A Male Version: HDMI 2.0 HDCP2.2 Transmission Direction: USB-C Male to HDMI A Male Interface Techniques: Gold-plated Resolution: 4K@60Hz Casing: Aluminum Alloy Jacket: PVC & Cotton Braided Cable OD: 4.5mm
		CRBBH	2M	
		AGHBF	1M	Color: Black Connector Type: HDMI C Male/HDMI A Male Interface Techniques: Gold-plated Transmission Direction: Dual Direction Resolution: 4K@60Hz Conductor: Pure Copper Jacket: PVC Casing: Single-colored Injection Cable OD: 5.2mm
		AGHBG	1.5M	
		AGHBH	2M	
		AGHBI	3M	
		ALABT	30M	Color: Black Connector Type: HDMI A Male Interface Techniques: Gold-plated Transmission Direction: HDMI A Male to HDMI A Male Resolution: 4K@60Hz Conductor: Tinned Copper & Optical fiber Jacket: PVC Casing: Zinc Alloy

Image	Packaging	Model Name	Length	Specifications
CABLE AND EXTENSION				
HDMI CABLE				
		AGIBF	1M	Color: Black Connector Type: HDMI D Male/HDMI A Male Interface Techniques: Gold-plated Transmission Direction: Dual Direction Resolution: 4K@60Hz Conductor: Pure Copper Jacket: PVC Casing: Single-colored Injection Cable OD: 5.2mm
		AGIBG	1.5M	
		AGIBH	2M	
		AGIBI	3M	
		AHCB D	0.5M	Color: Black Interface Version: HDMI 2.0 Resolution: 4K@60Hz Wire Gauge: 30AWG Conductor Material: copper clad steel Outer Cover: PVC OD: 7.3mm
		AHCBF	1M	
		AHCBG	1.5M	
		AHCBH	2M	
		AHCB I	3M	
		AHCB J	5M	
DVI CABLE				
		ABFBD	0.5M	Color: Black Connector Type: HDMI Male/DVI (24+1)Male Interface Techniques: Gold-plated Transmission Direction: Dual Direction Resolution: DVI to HDMI: 4K@60Hz/HDMI to DVI: 1080P@60Hz Conductor: Pure Copper Jacket: PVC Casing: Single-colored Injection Cable OD: 7.3mm/8mm
		ABFBF	1M	
		ABFBG	1.5M	
		ABFBH	2M	
		ABFBI	3M	
		ABFB J	5M	
DISPLAY PORT TO HDMI				
		HBOB0	--	Color: Black Connector Type: HDMI A Female/DP Male Interface Techniques: Gold-plated Transmission Direction: DP Male to HDMI A Female Resolution: 1080P@60Hz Casing: PVC Size: 40.2mm*23.9mm*11.5mm
		HBPB0	--	
PRINTER CABLE				
		VAS-A16-B100	1M	USB2.0 A Male to B Male Print Cable Conductor: Tinned copper Transmission: 480Mbps Shielding: Aluminium foil+Metal braid Jacket: PVC
		VAS-A16-B150	1.5M	
		VAS-A16-B200	2M	
		VAS-A16-B300	3M	
		VAS-A16-B500	5M	
USB EXTENSION				
		VAS-A44-B100	1M	USB2.0 Extension Cable Conductor:Copper Speed:480Mbps Jacket:PVC
		VAS-A44-B150	1.5M	
		VAS-A44-B200	2M	
		VAS-A44-B300	3M	
		VAS-A44-B500	5M	
		VAS-A45-B100	1M	USB3.0 Extension Cable 1M Black Conductor:Copper Speed:5Gbps Shielding:Aluminum Foil Jacket:PVC
		VAS-A45-B150	1.5M	
		VAS-A45-B200	2M	
		VAS-A45-B300	3M	
		CBLHF	1M	Color: Gray Protocol: USB 3.0 Connector Type: USB-A Male/USB-A Female Transmission Rate: 5Gbps Rated Current: 2A Casing: Aluminum Alloy Jacket: PVC & Cotton Braided Conductor: Tinned Copper Interface Techniques: Nickel-plated
		CBLHH	2M	
		CBLHI	3M	

Image	Packaging	Model Name	Length	Specifications
CABLE AND EXTENSION				
DP CABLE				
		HCELG	1.5M	Color: Blue Connector Type: DP Male Interface Techniques: Gold-plated Transmission Direction: DP Male to DP Male Resolution: 8K@60Hz Conductor: Copper-clad steel + Silver Ion Wire Jacket: PVC & Cotton Braided Casing: Aluminum Alloy Cable OD: 6.3mm
		HCELH	2M	
		HCELJ	5M	
		HAKBG	1.5M	Color: Black Interface: DP Male Electroplating process: Gold-Plated Transmission direction: DP to DP Resolution: 4K@60Hz Conductor: SPCCS (Silver Plated Copper Clad Steel) Jacket: PVC Shell: PVC OD: 6.0mm
		HAKBH	2M	
		HAKBI	3M	
		HAKBJ	5M	
		HAKBL	10M	
		HFOBF	1M	Color: Black Interface: DP Male/HDMI Male Electroplating process: Gold-Plated Transmission direction: DP to HDMI Resolution: 4K@30Hz Conductor: Bare copper Jacket: PVC Shell: PVC OD: 6.0mm
		HFOBAC	1.8M	
		HFOBI	3M	
		HFOBJ	5M	
		HCCBF	1M	Color: Black Connector Type: DP Male Interface Techniques: Gold-plated Transmission Direction: DP Male to DP Male Resolution: 8K@60Hz/4K@120Hz Conductor: SPCCS (Silver Plated Copper Clad Steel) Jacket: PVC & Cotton Braided Casing: ABS Cable OD: 6.5mm/7.5mm
		HCCBG	1.5M	
		HCCBH	2M	
		HCCBI	3M	
		HCCBJ	5M	
		HCCBL	10M	
		CGYBF	1M	Color: Black Connector Type: USB-C Male/DP Male Version: DP 1.4 Transmission Direction: USB-C Male to DP Male Interface Techniques: Gold-plated Resolution: 8K@60Hz/4K@120Hz Casing: ABS & PVC Jacket: PVC Cable OD: 5.0mm
		CGYBG	1.5M	
		CGYBH	2M	
		CGZBH	2M	Color: Gray Connector Type: USB-C Male/DP Male Version: DP 1.2 Transmission Direction: USB-C Male to DP Male Interface Techniques: Gold-plated Resolution: 4K@60Hz/2K@144Hz Casing: Aluminum Alloy Jacket: PVC Cable OD: 4.5mm
NETWORK CABLE				
CAT 6				
		IBEBF	1M	Color: Black Connector Type: RJ45 8P8C Transmission Rate: 1000Mbps Bandwidth: 250MHz Conductor: Copper-Clad Aluminum Jacket: PVC Casing: PVC Cable OD: 5.5mm
		IBEBH	2M	
		IBEBI	3M	
		IBEBJ	5M	
		IBEBL	10M	
		IBEBN	15M	
		IBEBQ	20M	
		IBEBT	30M	
CAT5e				
		VAP-A10-S075	0.75M	Color: White Connector Type: RJ45 8P8C Transmission Rate: 100Mbps Bandwidth: 155MHz Conductor: Copper-Clad Aluminum Jacket: PVC Casing: PVC Cable OD: 5.5mm
		VAP-A10-S100	1M	
		VAP-A10-S150	1.5M	
		VAP-A10-S200	2M	
		VAP-A10-S300	3M	
		VAP-A10-S500	5M	
		VAP-A10-S1000	10M	
		VAP-A10-S1500	15M	
		VAP-A10-S2000	20M	

Image	Packaging	Model Name	Length	Specifications
NETWORK CABLE				
CAT 8				
		IKABD	0.5M	Color: Black Connector Type: RJ45 8P8C Interface Techniques: Gold-plated Transmission Rate: 40Gbps Bandwidth: 2000MHz Conductor: Oxygen-free Copper Shield: Aluminum Foil & Metal Braided Jacket: PVC Casing: PVC Cable OD: 6.3mm
		IKABF	1M	
		IKABG	1.5M	
		IKABH	2M	
		IKABI	3M	
		IKABJ	5M	
		IKABL	10M	
		IKABN	15M	
IKABQ	20M			
		IKJBF	1M	Color: Black Interface: RJ45 8P8C Shell: PVC + Copper Conductor: Oxygen-free copper Wire gauge: 26AWG Shielding: Aluminum foil + Aluminum Magnesium braid Jacket: PVC + Cotton braided OD: 7.5mm Bandwidth: 2000MHz Transmission speed: 40Gbps
		IKJBG	1.5M	
		IKJBH	3M	
		IKJBJ	5M	
		IKJBL	10M	
VGA CABLE				
		DAEBG	1.5M	Name: VGA(3+6) Cable Interface Techniques: Gold-plated Conductor: Pure Copper Shielding: Aluminum Foil+Braided Resolution: 1080P 60Hz Jacket: PVC Cable OD: 7.5mm/10mm
		DAEBH	2M	
		DAEBI	3M	
		DAEBJ	5M	
		DAEBL	10M	
USB Car Bluetooth Audio Receiver				
		NAGHG	1.5M	Color: Gray Interface type: USB 2.0 A Male/3.5mm Male Interface technics: Nickel-plated Shell: Zinc alloy Conductor: Enameled copper Jacket: PU Bluetooth version: 5.0 Bluetooth protocol: A2DP/HFP Audio decoding format: SBC/AAC Transmission distance: 10m barrier-free transmission
AUDIO CABLE				
		BAEBF	1M	Color: Black Connector Type: Optical Fiber Male Interface Techniques: Gold-plated Conductor: PMMA Jacket: PVC Casing: PVC
		BAEBG	1.5M	
		BAEBH	2M	
		BAEBI	3M	
		BAEBJ	5M	
ADAPTER				
HDMI ADAPTER				
		ACRBB	0.15M	Color: Black Connector Type: HDMI A Male/VGA Female/3.5mm Female/USB 2.0 Micro-B Female Interface Techniques: Gold-plated Transmission Direction: HDMI A Male to VGA Female Resolution: 1080P@60Hz Conductor: Tinned Copper Jacket: PVC Casing: ABS Rated Input: 5V/1A Size: 45mm*45mm*11mm
USB BLUETOOTH 5.1 ADAPTER				
		NAFB0	--	Color: Black Bluetooth version: 5.0 Transmission distance: 20m barrier-free transmission Interface type: USB-A Interface technology: Gold-plated Shell: ABS
USB ADAPTER				
		CDWB0	--	Color: Black Protocol: USB 2.0 Connector Type: USB-A Male/USB-C Female Interface Techniques: Nickel-plated Transmission Rate: 480Mbps Casing: PVC

Image	Packaging	Model Name	Length	Specifications
ADAPTER				
USB ADAPTER				
		CCSBB	0.15M	Color: Black Protocol: USB 2.0 Connector Type: USB-C Male/USB-A Female Interface Techniques: Nickel-plated Transmission Rate: 480Mbps Rated Current: 2A Conductor: Tinned Copper Shield: Aluminum Foil Casing: PVC Jacket: PVC
		CCUBB	0.15M	Color: Black Protocol: USB 2.0 Connector Type: Micro-B Male/USB-A Female Interface Techniques: Nickel-plated Transmission Rate: 480Mbps Rated Current: 2A Conductor: Tinned Copper Shield: Aluminum Foil Casing: PVC Jacket: PVC
		CCVBB	0.15M	Color: Black Protocol: USB 3.0 Connector Type: USB-C Male/USB-A Female Interface Techniques: Nickel-plated Transmission Rate: 5Gbps Rated Current: 2A Conductor: Tinned Copper Shield: Aluminum Foil & Metal Braided Casing: PVC Jacket: PVC
		CDIB0	--	Interface Type: Micro USB, Type C, USB 3.0 Interface Process: Nickel Plated / OTG Adapter Shell Material: PVC
		CDTB0	--	Color: Black Protocol: USB 2.0 Connector Type: USB-C Male/USB-A Female Interface Techniques: Nickel-plated Transmission Rate: 480Mbps Casing: PVC
		CDUB0	--	Color: Black Protocol: USB 3.0 Connector Type: USB-C Male/USB-A Female Interface Techniques: Nickel-plated Transmission Rate: 480Mbps Casing: PVC
		CDVB0	--	Color: Black Version: USB 2.0 Interface: Micro USB Male/USB-A Female Electroplating Process: Nickel-Plated Data Transfer Rates: 480Mbps Shell: PVC
		CDQH0	--	Color: Gray Protocol: USB 3.0 Connector Type: USB-C Male/USB-A Female Interface Techniques: Nickel-plated Transmission Rate: 5Gbps Casing: Aluminum Alloy
		CDPH0	--	Color: Gray Protocol: USB 3.0 Connector Type: USB-A Male/USB-C Female Interface Techniques: Nickel-plated Transmission Rate: 5Gbps Casing: Aluminum Alloy
		CEGBB	0.15M	Color: Black Connector Type: USB-A/RJ45 Interface Techniques: Gold-plated Network: 10/100Mbps Device Supported: PC/Mac/Android Device PnP Supported: Win 10/8/7/Vista/XP; Linux; Mac OS System Supported: Win 10/8/7/Vista/XP; Linux; Mac OS Network Environment: IPv4/IPv6 Shield: Aluminum Foil Casing: ABS
		HBCBB	0.15M	Color: Black Connector Type: Mini DP Male/HDMI A Female Interface Techniques: Gold-plated Transmission Direction: Mini DP Male to HDMI A Female Resolution: 4K@30Hz Conductor: Tinned Copper Jacket: PVC Casing: ABS Size: 45mm*40mm*15.5mm

Official Philippine Distributor

Image	Packaging	Model Name	Length	Specifications
ADAPTER				
USB ADAPTER				
		CDRBB	0.15M	Color: BlackConnector: USB-A Male/TRRS 35mm FemaleITRS 3.5mm Audio Female/TRS 3.5mm Mic FemaleInterface Techniques: Nickel-plated Audio Channel: 2.1Sampling Rate: 44.1/48k@16bitCasing: ABSFeatures: Adjustable Volume/ Mute Button
		CDRBD	0.5M	
		CDRBF	1M	
USB-C Male to 3.5MM Earphone Jack With DAC Adapter				
		BGMHA	0.1M	Color: Gray Connector Type: USB-C Male/3.5mm Female Interface Techniques: Nickel-plated Conductor: Enamelled Copper Jacket: TPE & Cotton Braided Casing: Aluminum Alloy
USB-A Male to 3.5MM Earphone Jack				
		VAB-S17-B	--	Color: Gray Connector Type: USB-A Male/TRS 3.5mm Audio Female/TRS 3.5mm Mic Female Interface Techniques: Nickel-plated Audio Channel: 2.1 Sampling Rate: 44.1/48k@16bit Casing: Aluminum Alloy
HDMI SWITCH				
		AKOB0	--	Color: Black Connector Type: HDMI Female Connector Technics: Gold-Plated Transmission Direction: Two-Way, 2 In 1 Out /1 In 2 Out Shell: ABS Resolution: 4K@60Hz
		AFFH0	--	Color: Gray 3 In 1 Out HDMI Switcher Gray Connector Type: HDMI A Female/DC 3.5mm Interface Techniques: Gold-plated Transmission Direction: HDMI IN to HDMI OUT Resolution: 4K@30Hz Casing: Aluminum Alloy & ABS Rated Input: 5V/1A Size: 105mm*59mm*20mm
		ACDG0	--	Color: Golden HDMI Switcher 5 in 1 Out Gold Connector Type: HDMI A Female/DC 3.5mm Interface Techniques: Gold-plated Transmission Direction: HDMI IN to HDMI OUT Resolution: 4K@30Hz Casing: Aluminum Alloy & ABS Rated Input: 5V/1A Size: 105mm*59mm*20mm
		ACCG0	--	Color: Golden 1 in 4 Out HDMI Splitter Black Connector Type: HDMI A Female/DC 3.5mm Interface Techniques: Gold-plated Transmission Direction: HDMI IN to HDMI OUT Resolution: 4K@30Hz Casing: Aluminum Alloy & ABS Rated Input: 5V/1A Size: 105mm*59mm*20mm
USB HUB				
USB-A HUB				
		CKOHB	--	Model:CKO Color: Gray Interface type: USB 3.0/USB 2.0x3 Interface technics: Nickel-plated Transmission speed:5Gbps(USB 3.0)/480Mbps(USB 2.0) Shell: Aluminum alloy & PC Conductor: Tinned copper Jacket: PVC Shielding: Aluminum foil & Metal braid Cable OD: 4.0mm

Image	Packaging	Model Name	Length	Specifications
USB HUB				
USB-A HUB				
		VAS-J43-B015	0.15M	Color: Black Connector Type: USB-A/USB 2.0x4 Interface Techniques: Nickel-plated USB Speed: 480Mbps (USB 2.0) Casing: ABS
		CKOHB	--	Model:CKO Color: Gray Interface type: USB 3.0/USB 2.0x3 Interface technics: Nickel-plated Transmission speed:5Gbps(USB 3.0)/480Mbps(USB 2.0) Shell: Aluminum alloy & PC Conductor: Tinned copper Jacket: PVC Shielding: Aluminum foil & Metal braid Cable OD: 4.0mm
		CHBBB	0.15M	Color: Black Connector Type: USB-A/USB 3.0x4/Micro-B Interface Techniques: Nickel-plated USB Speed: 5Gbps (USB 3.0) Rated Input: 5V – 0.5A Casing: ABS
		CHABB	0.15M	Color: Black Connector Type: USB-A/USB 3.0x1/USB 2.0x3/Micro-B Interface Techniques: Nickel-plated USB Speed: 480Mbps (USB 2.0)/5Gbps (USB 3.0) Rated Input: 5V – 0.5A Casing: ABS
		TGKBB	0.15M	Color: Black Connector Type: USB-A/USB 2.0x4 Interface Techniques: Nickel-plated USB Speed: 480Mbps (USB 2.0) Casing: ABS
		CHPBB	0.15M	Color: Black Connector Type: USB-A/USB 2.0x3/RJ45/Micro-B Interface Techniques: Nickel-plated USB Speed: 480Mbps (USB 2.0) Network: 10/100Mbps Rated Input: 5V–2A Casing: ABS
		CHNBB	0.15M	Color: Black Connector Type: USB-A/USB 3.0x3/RJ45/Micro-B Interface Techniques: Nickel-plated USB Speed: 5Gbps (USB 3.0) Network: 10/100/1000Mbps Rated Input: 5V–2A Casing: ABS
USB-C HUB				
		TGOBB	0.15M	Color: Black Connector Type: USB-C/USB 2.0x3/RJ45/Micro-B Interface Techniques: Nickel-plated USB Speed: 480Mbps (USB 2.0) Network: 10/100Mbps Rated Input: 5V–2A Casing: ABS
		TGPBB	0.15M	Color: Black Connector Type: USB-C/USB 3.0x3/RJ45/Micro-B Interface Techniques: Nickel-plated USB Speed: 5Gbps (USB 3.0) Network: 10/100/1000Mbps Rated Input: 5V–2A Casing: ABS
		TOJHB	--	7 in 1 Color: Gray Connector Type: USB-C/HDMI/USB 3.0x3/SD/TF/PD Interface Techniques: Nickel-plated Resolution: 4K@30Hz USB Speed: 5Gbps (USB 3.0) Card Slot: 3.0 SD/TF 2-LUN (Dual-slot Available Simultaneously) Rated Input: PD 100W Casing: Aluminum Alloy & ABS
		TOLHB	--	9 in 1 Color: Gray Connector Type:USB-C/HDMI/USB 3.0x3/RJ45/SD/TF/ TRRS 3.5mm/PD Interface Techniques: Nickel-plated Resolution: 4K@30Hz USB speed: 5Gbps (USB 3.0) Network: 10/100/1000Mbps Card slot: 2.0 SD 1-LUN (Single-slot available simultaneously) Audio Jack: 48k@16bit for OMTP&CTIA Power supply: PD 100W

Image	Packaging	Model Name	Length	Specifications
CABLE MANAGER				
		KBRB0	--	Slot diameter: 6mm / Desktop Cable Manager Material: Silica gel Attachment Method: 3M Adhesive Ports QTY: 5
		KBRB0-2	--	
HARD CASE POUCH				
		KBJB0	--	Color: black / Storage hard Case Shell: PU Size: 16*9*3c
USB-C CABLE				
		TAXWD	0.5M	Color: White Protocol: USB 2.0 Connector Type: USB-C Male/USB-C Male Interface Techniques: Nickel-plated Transmission Rate: 480Mbps Rated Current: 3A Conductor: Tinned Copper Shield: Aluminum Foil & Metal Braided & GND Casing: PVC Jacket: PVC
		TAXWF	1M	
		TAXWG	1.5M	
		TASWF	1M	Color: White/Black Version: USB 2.0 Interface: USB-C Male/Lightning Male Electroplating Process: Nickel-Plated Data Transfer Rates: 480Mbps Output Current: 3A Conductor: Tinned Copper Shielding: Aluminum Foil & Metal Braid Shell: ABS Jacket: TPE Certification: MFi
		TASWH	2M	
STAND HOLDER				
		KDLI0	--	Color: Silver Net weight: 225g Static load: About 30Kg Size: 247*210*65-95mm Accessories: Exquisite Flannel Bag
		KDNW0	--	Color: White Shell: ABS Adjustable Viewing Angles: 9 Angles Net Weight: 145g Size: Storage Size: 246mm*50mm*22mm Unfolded Size: 246mm*172.3mm*170.2mm
CHARGER				
		FADB0-US	--	Protocol: PPS/PD3.0/QC4.0/AFC/FCP/BC1.2/Apple 2.4A Output: 5V==3A; 9V==2.22A; 12V==1.67A (20W max) Qualification: CE;UKCA;FCC;RoHS2.0; PD 20W for iPhone 13 iPhone 13 Mini series!
		FADW0-US	--	
		FEGB0-US	--	Shell:PC Input: 100-240V~50/60Hz 2A Output (USB-C 1): 5V==3A; 9V==3A; 12V==3A; 15V==3A; 20V==5A(100W MAX) Output (USB-C 2): 5V==3A; 9V==3A; 12V==3A; 15V==3A; 20V==5A(100W MAX) Output (USB-A): 4.5V==5A; 5A==4.5V; 9V==3A; 12V==2.5A; 20V==1.5A(30W MAX) Multi output: USB-C 1+ USB-C 2: 65W+30W USB-C 1+USB: 65W+30W USB-C 2+USB: 25W(5V/5A) USB-C 1+ USB-C 2+USB: 65W(USB-C 1)+25W(USB-C 2+USB) Protocol(USB-C 1):PD3.0/PPS/QC4.0+/AFC/FCP/SCP/PE2.0/SFCP/Apple 2.4A Protocol(USB-C 2):PD3.0/PPS/QC4.0+/AFC/FCP/SCP/PE2.0/SFCP/Apple 2.4A Protocol(USB-A):QC3.0/SCP/FCP/AFC/PE2.0/SFCP/Apple 2.4A
		FEGW0-US	--	
		FFEH0	--	Shell: Aluminum alloy & ABS Input: DC 12-24V Output(USB 1):5V- 3A9V- 2A1V 1.5A Output(USB 2):5V- 3A9V- 2A12V- 1.5A Total output: 5V-- 3.4A(17W MAX) Protocol(USB 1):QC3.0/FCP/AFC/BC1.2/Apple 2.4A Protocol(USB 2):QC3.0/FCP/AFC/BC1.2/Apple 2.4A

Image	Packaging	Model Name	Length	Specifications
CARD READER				
		CLIH0	--	Color: Gray Connector Type: USB 3.0-A Male/SD/TF Interface Techniques: Nickel-plated Card Slot: 3.0 SD/TF 2-LUN (Dual-slot Available Simultaneously) Transmission Rate: 5Gbps (USB 3.0) Casing: Aluminum Alloy & ABS
		CLEB0	--	Color: Black Interface: USB 2.0-A Male/SD/TF Interface techniques: Nickel-plated Card slot: 2.0 SD/TF 1-LUN (Single-slot Available Simultaneously) Transmission Rate: 480Mbps (USB 2.0) Casing: ABS & PC
USB WIFI DONGLE				
		KDSB0	--	Color: Black Connector Type: USB-A/USB 3.0x3/RJ45/Micro-B Interface Techniques: Nickel-plated USB Speed: 5Gbps (USB 3.0) Network: 10/100/1000Mbps Rated Input: 5V-2A Casing: ABS
M.2 SSD ENCLOSURE				
		KPEH0	--	Color: Gray Interface: USB 3.1 Gen 1-C Interface techniques: Nickel-plated Hard disk interface: M.2 NGFF (B-Key/B&MKey) Hard disk parameter: 2230/2242/2260/2280 Transmission Rate: 5Gbps Casing: Aluminum Alloy
DOCKING STATION				
		TPJH0-US	--	12 in 1 Color: Gray Connector Type: USB-C/HDMI/VGA/USB 3.1 Gen 2/USB 3.1 Gen 2-C/USB 3.0x2/RJ45/SD/TF/TRRS 3.5mm/PD/DC 3.5mm Interface Techniques: Nickel-plated Resolution: 4K@30Hz (HDMI)/1080P@60Hz (VGA)/1080P@60Hz (HDMI+VGA) USB Speed: 10Gbps (USB 3.1 Gen 2/USB 3.1 Gen 2-C)/5Gbps (USB 3.0) Network: 10/100/1000Mbps Card slot: 3.0 SD/TF 2-LUN (Dual-slot Available Simultaneously) Audio Jack: OMTP & CTIA Power supply: PD 100W/DC 10W
EAR BUDS				
		NBGW0	--	Color: White/Black Interface Type of Charging Case: USB-C Protocol: Bluetooth 5.3 Bluetooth Profile: AVRCP/A2DP/HFP/HSP Audio Codec: SBC/AAC Bluetooth Frequency Band: 2402MHz-2480MHz Frequency Range: 20Hz-20KHz Interface Techniques: Nickel-Plated Effective Range: ≤10m Casing: ABS
		NBGB0	--	
		NBIB0	--	Bluetooth Version: Bluetooth 5.3 Compatible Bluetooth profile: AVRCP/A2DP/HFP/HSP Supported Codec: SBC/AAC Maximum Communication range: ≤10 m Frequency Band: 2402MHz-2480MHz Frequency Range: 20Hz-20KHz Earbuds' Battery Capacity: 40mAh/0.148Wh Earbuds' Input Power: 5V 40mA Charging Case's Battery capacity: 300mAh/1.11Wh Charging Case's Input Power: 5V 300mA Charging Case's Interface: USB-C Shell: ABS
		NBIBW0	--	